

Product Change Notification



PCN DETAILS

REFERENCE

PCN-2025-03

ISSUE DATE

20th June 2025

EFFECTIVE DATE

Immediate. Unless specified we will continue to ship previous X & Y driver code models until stock is exhausted.

KEY CHANGES

PHYSICAL

Input wires now have 3 conductors. 1 x common negative and 2 x positive (connect only one)

ELECTRICAL

X & Y Driver codes were 12-24VAC / 24VDC. E driver code are 24VDC only.

Input cables will have 3 conductors. Black, White, Yellow. See label for connection instructions.

Can be dimmed using DALI or TRIAC power supplies just like Neon Flex or Strip Lights.

OPTICAL

Previous models were 3000K only. New models are 2700K or 3000K.

CHANGE SUMMARY

Aqualux is pleased to announce the arrival of it's new Dual CCT 2-Wire Dimmable products in the Hydra Range. The roll out of these products will happen progressively over the coming months and will replace old versions when stock runs out. New datasheets and IES files will be available online soon.



PRICE CHANGES

Please contact the office for updated prices for Dual CCT models

AQP-LU-Z-34 LABEL
www.aqualux.com.au

ATTENTION!

Do NOT connect both channels.

| | |
|-----------------|-------------------------|
| Common Negative | Black Wire 24VDC - |
| 3000K | White Wire 24VDC +ve |
| OR | |
| 2700K | Yellow Wire 24VDC +ve |

SUPPORT

www.aqualux.com.au
AQP-LU-Z-34 LABEL

- 24VDC and parallel wiring only
- For wattage see product label or refer to website
- Do not connect more than 1 LED channel
- Ensure cable joins are fully sealed including the outer sheath
- Your warranty depends on correct installation.

If you are in doubt please contact Aqualux at 0294547900 or sales@aqualux.com.au or visit our support page (QR)

CONTACT US:

For further information, please contact your representative or our office at **02-9454-7900** or via email at sales@aqualux.com.au.

+61-2-9454-7900
www.aqualux.com.au

Product Change Notification



| Code | Description | Color | Electrical | Watts | CCT | Glass | Cable | Status |
|----------------------|-------------------------|------------|-----------------------------|-------|---------------|-----------------|---------------|--------------|
| AQL-416-B2-E007DWDCS | Mushroom Bollard | Black | 24VDC 2-Wire Dimming | 7w | 2700K + 3000K | Diffuse Clear | Standard Tail | New |
| AQL-416-B2-Y00730DCS | Mushroom Bollard | Black | 12-24VAC 24VDC Non-Dimmable | 7w | 3000K | Diffuse | 1m Std Cable | Run out |
| AQL-416-B3-E007DWDCS | Mushroom Bollard | Aged Brass | 24VDC 2-Wire Dimming | 7w | 2700K + 3000K | Diffuse Clear | Standard Tail | New |
| AQL-416-B3-Y00730DCS | | | | | | | | Discontinued |
| AQL-417-B2-E004DWDFS | Step Light | Black | 24VDC 2-Wire Dimming | 4w | 2700K + 3000K | Diffuse Frosted | Standard Tail | New |
| AQL-417-B2-Y00430DFS | | | | | | | | Discontinued |
| AQL-417-B3-E004DWDFS | Step Light | Aged Brass | 24VDC 2-Wire Dimming | 4w | 2700K + 3000K | Diffuse Frosted | Standard Tail | New |
| AQL-417-B3-Y00430DFS | Eyelid Steplight | Aged Brass | 12-24VAC 24VDC Non-Dimmable | 4w | 3000K | Diffuse | 1m Std Cable | Run out |
| AQL-418-B2-E004DWDFS | Step Light | Black | 24VDC 2-Wire Dimming | 4w | 2700K + 3000K | Diffuse Frosted | Standard Tail | New |
| AQL-418-B2-Y00430DFS | Slotted Steplight | Black | 12-24VAC 24VDC Non-Dimmable | 4w | 3000K | Diffuse | 1m Std Cable | Run out |
| AQL-418-B3-E004DWDFS | Step Light | Aged Brass | 24VDC 2-Wire Dimming | 4w | 2700K + 3000K | Diffuse Frosted | Standard Tail | New |
| AQL-418-B3-Y00430DFS | Slotted Steplight | Aged Brass | 12-24VAC 24VDC Non-Dimmable | 4w | 3000K | Diffuse | 1m Std Cable | Run out |
| AQL-419-B2-E002DWDCS | Step Light | Black | 24VDC 2-Wire Dimming | 2w | 2700K + 3000K | Diffuse Clear | Standard Tail | New |
| AQL-419-B2-Y00230DCS | | | | | | | | Discontinued |
| AQL-419-B3-E002DWDCS | Step Light | Aged Brass | 24VDC 2-Wire Dimming | 2w | 2700K + 3000K | Diffuse Clear | Standard Tail | New |
| AQL-419-B3-Y00230DCS | | | | | | | | Discontinued |
| AQL-420-B2-E007DWDFS | Step Light | Black | 24VDC 2-Wire Dimming | 7w | 2700K + 3000K | Diffuse Frosted | Standard Tail | New |
| AQL-420-B2-Y00730DFS | Rect. Slotted Steplight | Black | 12-24VAC 24VDC Non-Dimmable | 7w | 3000K | Diffuse | 1m Std Cable | Run out |
| AQL-420-B3-E007DWDFS | Step Light | Aged Brass | 24VDC 2-Wire Dimming | 7w | 2700K + 3000K | Diffuse Frosted | Standard Tail | New |
| AQL-420-B3-Y00730DFS | Rect. Slotted Steplight | Aged Brass | 12-24VAC 24VDC Non-Dimmable | 7w | 3000K | Diffuse | 1m Std Cable | Run out |

CONTACT US:

For further information, please contact your representative or our office at **02-9454-7900** or via email at sales@aqualux.com.au.

+61-2-9454-7900
www.aqualux.com.au